



I N D U S T R I A S

sambara

PINTURAS LAGUN



C/José María de Pereda, 26 (Madrid)



913 672 516



648 270 241



comercial@pinturaslagun.es

pinturaslagun.es

Enlace ficha producto



NITROSAN BLANCO

FEATURES

NITROSÁN BLANCO is a family of pigmented topcoats formulated with nitrocellulose as a base. This products are created for application on MDF and all wood surfaces. They contains high degree of on volatile matter and therefore have an excellent silky touch.

HOW TO USE

1-component product

Mix with solvent until adequate level of viscosity has been reach when used with spray guns or others air-pressure equipments.

Application with brush is recommended

Surfaces must be clean, in sound condition and free of grease.

Possible application with airmix and airless.

PROPIEDADES

	MATE	SAT	BRILLO		
Viscosity	60 - 100	90 - 110	100 - 150	sec	Ford 4 at 20°C
Density	1.08 - 1.10	1.09 - 1.11	1.08 - 1.10	g/cm ³	ISO 2811
Non volatile matter	43 - 45	40 - 42	42 - 44	%	2h at 120°C
Gloss	12 - 16	35 - 45	90 - 100		(gloss a 60°)

RECOMMENDED SOLVENTS: NC solvent, Poliurethane Solvent, Universal solvent

PACKING AND STORAGE

1kg, 5kg, 25kg and 200kg. Can be stored up to 6 months after the product production date in original unopened container. Please keep away from freezing temperature and high temperatures, must be kept between 5° and 30° C.

OTHER DATA

These suggestions and data are based on information we believe to be reliable.

They are offered in good faith but without guarantee.

For more information on security and manipulation, read the corresponding FS.

INDUSTRIAS SAMBARA SL

Ctra. de Belvis, Km. 1,200

Teléf.: 91 658 04 45* - Fax: 91 658 07 19

28860 PARACUELLOS DE JARAMA (Madrid)

e-mail: info@industrias-sambara.com

www.industrias-sambara.com

