



PINTURAS LAGUN

📍 C/José María de Pereda, 26 (Madrid)

📞 913 672 516 📞 648 270 241

@ comercial@pinturaslagun.es

pinturaslagun.es

Enlace ficha producto





VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
C.F./P.IVA/ R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.
www.valpaint.it E-mail: info@valpaint.it

SC 00031

GUMMIFLEX WHITE AND COLOURED

Technical Sheet

NAME:

TYPE:

USE:

GUMMIFLEX WHITE AND COLOURED

mural and anti-smoke paint, with odourless solvent base
exterior surfaces painting. Used for interior surfaces where good
resistance to washing is requested. For yellowed ceilings and walls owing
to smoke and steam

TECHNICAL DATA:

specific weight: 1.400 ± 30 gr/lt at 25°C
viscosity: 20" Coppa Ford 8 at 25°C
yield: 6 - 7 m²/lt.
aspect: opaque
colours: white and colour from the catalogue
packaging: cans of 1 LT. - 5 LT. - 18 LT.
on the surface: 3 hours at 20°C
over painting: 6 hours at 20°C
below the surface: 24 hours at 20°C, depending on atmospheric
conditions

DRYING TIME:

CHARACTERISTICS AND RESISTANCE:

excellent resistance to atmospheric agents, also in extreme conditions
(maritime climate, industrial zones). Insensitive to the alkalines which
cause the disintegration of the protection of paints. Resistant to water but
gas-permeable (transpirability). High level of washability. Excellent to
cover smoke and nicotine impregnated walls.

PREPARATION OF THE SURFACE:

value the surface condition, removing old and not anchored paints and
plastering again where necessary. Fills cracks and holes with Stucco Fast
150

PREPARATION OF THE PRODUCT:

thinning: ready for use. Thin out at 10% apx. with
odourless thinner or white spirit, if applied by
spray gun.

catalization relation: = = =

pot life: = = =

APPLICATION:

system: with brush, roller or spray gun
coats: 1 - 2

NOTE:

Compared with traditional water paints, Gummiflex has the following advantages:

- 1) Does not contain water-sensitive (better resistance to water)
- 2) Does not contain biodegradable components (better resistance to water)
- 3) Excellent covering on stained walls with smoke.
- 4) Is not affected by chemical products of smog (absorbs less dirt)
- 5) Can be applied in low temperatures to + 5°C.
- 6) Is breathable and does not cause bubbles
- 7) Is therefore insensitive to the alkalines (frequent cause of the disintegration of the paint)
- 8) Penetrates deeper and so ensures better binding
- 9) Is not affected by rain which can fall after the exterior application
- 10) Wash tools with white spirit or synthetic solvent

Technical Sheet no. SC 00031 issued by the Control Quality Technician
Edition. No. 4 June 2008